


折疊式集裝箱用材參數及報價單

產品效果圖



專案	序號	名稱	詳細描述	尺寸規格	數量	單位	
	一	型式一 (Form 1)	標準箱 (Standard container)	外部尺寸: 2500mm (長)*5800mm (寬)*2390mm (高) 內部尺寸: 2370mm (長)*5635mm (寬)*2265mm (高) 折疊尺寸: 2500mm (長)*5800mm (寬)*360mm (高) 重量: 1.1t 40尺高櫃: 12套	1	套	
	1	框架 (Frame)	頂主梁 (Top girder)	異形型鋼鍍鋅凹凸管63mm*80mm*1.5mm (兩側) Special shaped steel galvanized concave convex pipe 63mm*80mm*1.5mm (both sides)	3	根	
			底主梁 (Bottom girder)	異形型鋼鍍鋅凹凸管63mm*120mm*1.5mm (兩側) Special shaped steel galvanized concave convex pipe 63mm*120mm*1.5mm (both sides)	3	根	
			頂部橫樑 (Top beam)	鍍鋅方管50mm*50mm*1.5mm Galvanized square pipe 50mm*50mm*1.5mm	6	根	
			頂部次橫樑 (Top sub-beam)	鍍鋅方管30mm*50mm*1.5mm Galvanized square pipe 30mm*50mm*1.5mm	3	根	
			前後端主梁上側 (Upper side of front and rear main beam)	鍍鋅方管60mm*60mm*1.5mm Galvanized square pipe 60mm*60mm*1.5mm	2	根	
			前後端主梁下側 (Lower side of front and rear main beam)	異形型鋼鍍鋅凹凸管63mm*80mm*1.5mm Special shaped steel galvanized concave convex pipe 63mm*80mm*1.5mm	4	根	
			側牆框架 (Sidewall frame)	異形型鋼鍍鋅凹凸管63mm*80mm*1.5 (兩側) Special shaped steel galvanized concave convex pipe 63mm*80mm*1.5 (both sides)	8	根	
			底部橫樑 (Bottom crossbeam)	鍍鋅方鋼管40mm*40mm*1.5mm Galvanized square steel pipe 40mm*40mm*1.5mm	14	根	
			鑄鋼駁接角件 (Cast steel butt joint Corner Fitting)	鋼板175mm*100mm*15mm Steel plate (175mm*100mm*15mm)	8	塊	

用 材 參 數			304不銹鋼合頁 (304 stainless steel hinge)	高強度鍍鋅合頁85mm*115mm*3mm (軸柱304不銹鋼) High-strength galvanized hinge85mm*115mm*3mm (Shaft column304stainless steel)	36	個	
			整體框架保護塗料 (Integral frame protective coating)	嘉寶莉高光瓷漆 Cabaret high gloss enamel	1	套	
	2	- 屋頂 (Top of container)	外部頂板 (External roof)	1040型彩鋼瓦 (0.45mm) 1040color steel tile (0.45mm)	6	套	
			內部吊頂 (Internal ceiling)	831型吊頂瓦 (0.28mm) 831 ceiling tile (0.28mm)	7	張	
			隔熱岩棉 (Insulation rock wool)	容重60kg/m³ Bulk density 60kg/m³*14.5square	18	m³	
	3	- 地面 (Floor)	A級防火布逸板 (Grade A fireproof glass magnesium plate)	15mm	5	張	
	4	- 牆 (Wallboard) (牆板可定制)	保溫隔熱岩棉彩鋼複合夾芯板 (側牆) Heat insulation rock wool color steel composite sandwich panel (side wall)	0.28mm彩鋼板/50mm/65kg/m³岩棉 0.28mm color steel plate / 50mm / 65kg / m³ rock wool	8	塊	
			保溫隔熱岩棉彩鋼複合夾芯板 (前後牆) Heat insulation rock wool color steel composite sandwich panel (Front and rear walls)	0.28mm彩鋼板/50mm/65kg/m³岩棉 0.28mm color steel plate / 50mm / 65kg / m³ rock wool	6	塊	
	5	-窗 (Window)	高端鋁合金防盜一體窗推拉系列 High-end aluminum alloy anti-theft integrated window sliding series(push-pull Series)	970mm*1215mm帶紗窗 970mm*1215mm(With screen window)	2	樞	

技術參數	6	- 門 (Door)	高端集裝箱專用鋼制防盜門 High-end container special steel anti-theft door	970mm*1970mm	1	檯	
	7	- 電氣系統 (Electrical system)	電路保護器 (circuit protector)		1	個	
			工業插頭插座（5孔） 〈Industrial plug and socket (5 holes)〉		1	個	
			單管LED燈 (Single tube LED light)		1	個	
			空調專用插座（3孔） 〈Special socket for air conditioner (3 holes)〉		1	個	
			燈開關 (Light switch)		1	個	
		屋面承重	≧ 50公斤/m²				
		樓面承重	≧ 150公斤/m²				
		走道承重	≧ 200公斤/m²				
		壁側壓力	≧ 80公斤/m²				
		防火級別	A級防火				
		牆變形係數	≦ 300公斤/m²				
		抗震等級	10級抗震				
		抗風等級	10級抗風				
		備註	本司折疊板房和市場上其他折疊板房的區別： 市場上其他折疊板房折疊處的型材直接採用方管，所有折疊處都要打膠或是加密封條才能起到密封作用，但是打膠是解決不了根本的漏水滲水問題的，幾場風雨過後，就會老化，出現縫隙，自然而然的漏水滲水問題就出現了，然後會給使用過程中增添很多麻煩和煩惱。萬合生產的折疊板房所有折疊處的型材是凹凸卡槽設計，型材自帶防水，不用打膠，不管是用到什麼時候，永久把風沙雨水，隔離在凹凸卡槽外面，也就是板房體的外面，不會滲進咱們的板房內部。折疊處的合頁是304不銹鋼軸心合頁，他使用的年限也比市場上的其他板房要長，它折疊的次數可以達到在1000次以上！				